



---

## PRICE LIST

Ref: RRKL/LP/BCISI/08-1/20  
w.e.f. 20th August 2020

THE ONLY INDIAN  
WIRE BRAND  
TRUSTED BY

85+

COUNTRIES  
GLOBALLY



**RR** KÄBEL  
WIRES & CABLES

**AKALMAND BANO,  
SAHI CHUNO.**

# AKALMAND BANO, SAHI CHUNO.



## BUILDING WIRES

**RR** KÄBEL  
WIRES & CABLES

INDIA'S ONLY WIRE WITH  
**REACH • RoHS**  
**CE • CPR** Compliant



## SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, FR PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	824	24
1.0	14/0.3	1117	20
1.5	22/0.3	1638	12
2.5	36/0.3	2616	12
4.0	56/0.3	3802	8
6.0	84/0.3	5666	4
10.0	140/0.3	10422	3
16.0	126/0.4	16737	2

## UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, HR FR PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	1180	20
1.5	37/0.23	1720	12
2.5	61/0.23	2754	12
4.0	61/0.29	4182	8
6.0	91/0.29	6218	8

## FLAMEX FR-LSH FR-LSH PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, FR-LSH PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	14/0.3	1169	20
1.5	22/0.3	1721	12
2.5	36/0.3	2742	12
4.0	56/0.3	3985	8
6.0	84/0.3	5918	4

Note: As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables.

## FIREX LSOH LOW SMOKE ZERO HALOGEN 90°C.



RR Kabel make Single Core unsheathed Electrolytic annealed multistrand bare copper conductor Low Smoke Zero Halogen (LSOH) Insulated Industrial Cables in Voltage grade upto and including 1100 Volts. (HSN Code : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	1401	20
1.50	22/0.3	2000	12
2.50	36/0.3	3160	12
4.00	56/0.3	4707	8
6.00	84/0.3	6818	4

\* LSOH - Conductor Conforming to IEC 60228 & Insulation Conforming to EN 60332-1-2 & 3, EN 60754-1 & 2.

## RR KABEL FR / FR-LSH / LSOH



Multistrand bright electrolytic annealed bare copper conductor, FR PVC/FR-LSH PVC/LSOH Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION	RR KABEL FR-LSH FR-LSH PVC INSULATION	RR KABEL LSOH LSOH INSULATION
0.75	24/0.2	8	1855	1920	2168
1.0	32/0.2	13	2469	2549	2784
1.5	30/0.25	17	3612	3738	3965
2.5	50/0.25	24	5828	6044	6427
4.0	56/0.3	30	8893	9204	9711
6.0	84/0.3	38	13222	13652	14404

Note: As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables.



## COMMUNICATION CABLES

**RR** KÄBEL  
**WIRES & CABLES**

- RATNA CO-X
- RATNA LAN
- RATNA COM
- CCTV CAMERA CABLE
- SPEAKER CABLE

## RATNA CO-X



RR Kabel make Electrolytic grade solid annealed bare copper conductor gas injected physical polyethylene foam insulated, wrapped with Aluminium Mylar tape and Al alloy wire braided, Jelly flooded and PVC Jacketing in Black Colour, Co-Axial Industrial Cables. (HSN Code : 8544)

RG 59 F		RG 6 F		RG 11 F	
100 Mtr.	305 Mtr.	100 Mtr.	305 Mtr.	100 Mtr.	305 Mtr.
1701	5188	2249	6859	5129	15643

## RATNA LAN



RR Kabel make Solid bare copper conductor 4 Pair unshielded twisted pair (UTP) Industrial cables for Computer Lan Network with Grey colour & FR PVC Jacket. (HSN Code : 8544)

CAT 5e		CAT 6	
100 Mtr.	305 Mtr.	100 Mtr.	305 Mtr.
2262	6899	3026	9229

## RATNA COM



RR Kabel make Solid Electrolytic annealed bare copper conductor Industrial Switchboard & Telephone Cables with high density polyethylene insulation, paired, polyester taped, Nylon Rip Cord and Grey colour sheathed with FR PVC, generally conform to "ITD specification S/WS 113 C" (HSN Code : 8544)

Dia	1 Pair	2 Pair	3 Pair	4 Pair	5 Pair	10 Pair	20 Pair
0.5 mm	666	1235	1783	2362	2911	5678	11396


## CCTV CAMERA CABLES



RR Kabel make Annealed Tinned copper conductor, PE Insulated, ATC Braided, Polyester tape screened, PVC outer sheathed Industrial CCTV Camera Cables.(HSN CODE : 8544)

Size	Packing	Rate Per Coil	No. of Coils packed in an Outer Box
3 + 1	100 Mtr.	3059	3
4 + 1	100 Mtr.	3465	3

## SPEAKER CABLES



RR Kabel make Multistrand Annealed bare copper conductor, PVC Insulated Industrial Speaker wires. (HSN CODE : 8544)

Size	Packing	Rate Per Coil	No. of Coils packed in an Outer Box
2C x 0.50	100 Mtr.	1433	10
2C x 0.75	100 Mtr.	1980	10
2C x 1.0	100 Mtr.	2552	8
2C x 1.5	100 Mtr.	3601	8
2C x 2.5	100 Mtr.	5862	8

\* 3% Extra for Transparent sheath



## INDUSTRIAL CABLES

**RR** KÄBEL  
**WIRES & CABLES**

- FLEXIBLE SINGLE CORE CABLE
- FLEXIBLE MULTICORE CABLES
- SHIELDED CABLE
- BRAIDED CABLE



## RR KABEL FR / FR-LSH / LSOH



Multistrand bright electrolytic annealed bare copper conductor, FR PVC/FR-LSH PVC/LSOH Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION	RR KABEL FR-LSH FR-LSH PVC INSULATION	RR KABEL LSOH LSOH INSULATION
10.0	140/0.3	52	11580	12159	12970
16.0	126/0.4	70	18596	19526	20828
25.0	196/0.4	88	29005	30165	32486
35.0	276/0.4	112	40572	42195	45441
50.0	396/0.4	146	57309	59601	64186
70.0	360/0.5	216	81997	85277	91837
95.0	480/0.5	262	109793	114185	122968
120.0	608/0.5	310	140062	145664	156869
150.0	750/0.5	355	173625	180570	194460
185.0	931/0.5	415	213211	221739	238796
240.0	1200/0.5	500	277800	288912	311136
300.0	1500/0.5	550	346807	360679	388424
400.0 *	2013/0.5	590	480503	499723	538163
500.0 *	2562/0.5	660	610867	635302	684171
630.0 *	3416/0.5	725	812021	844502	909464

The item marked \* are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

## RATNA FLEX SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	650
0.75	24/0.2	8	937
1.0	32/0.2	13	1209
1.5	30/0.25	17	1747
2.5	50/0.25	24	2824
4.0	56/0.3	30	4431
6.0	84/0.3	38	6565

Note: As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables.

## RATNA FLEX MULTICORE CABLES



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Rate per 100 meter											
Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE	Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE
0.5	16/0.2	5	1923	2579	3330	25.0	196/0.4	88	67784	95154	127175
0.75	24/0.2	8	2562	3451	4570	35.0	276/0.4	112	-	133513	178626
1.0	32/0.2	13	3178	4263	5564	50.0	396/0.4	146	-	189685	253019
1.5	30/0.25	17	4178	5828	7700	70.0	360/0.5	216	-	272029	360356
2.5	50/0.25	24	6677	9347	12395	95.0	480/0.5	262	-	365230	478895
4.0	56/0.3	30	10303	14592	19114	120.0	608/0.5	310	-	461085	610661
6.0	84/0.3	38	14927	21497	28285	150.0	750/0.5	355	-	585285	767657
10.0	140/0.3	52	26252	37425	49238	185.0	931/0.5	415	-	719190	933919
16.0	126/0.4	70	41405	58470	78177	240.0	1200/0.5	500	-	934689	1263052
						300.0	1500/0.5	550	-	1165919	1577668

## CONTROL CABLES



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

Rate per 100 meter												
Size (Sq.mm)	CONFIG.	AMPS	5 CORE *	6 CORE *	7 CORE *	8 CORE *	10 CORE *	12 CORE *	14 CORE *	16 CORE *	19 CORE *	24 CORE *
0.5	16/0.2	5	4461	5157	5859	6890	8631	10137	11513	13039	15386	19694
0.75	24/0.2	8	6086	7464	8124	9740	12149	14450	16452	18950	22848	28619
1.0	32/0.2	13	7733	8847	10174	11771	15110	17748	20589	23531	29013	35707
1.5	30/0.25	17	10505	12777	14476	16652	21478	25334	29495	33223	39309	50366
2.5	50/0.25	24	17240	20798	23829	27364	34816	41002	47639	54976	64145	82081
4.0	56/0.3	30	26128	32432	37471	44128	55687	65966	76826	87562	103441	132161
6.0	84/0.3	38	40109	48508	56533	64772	82763	98102	113719	129522	152838	195010
10.0	140/0.3	52	68485	-	-	-	-	-	-	-	-	-
16.0	126/0.4	70	105852	-	-	-	-	-	-	-	-	-

Loading factor for Different Insulation / Sheath \* -

FR Insulation	FR Sheath	FR-LSH / HR Insulation	FR-LSH / HR Sheath	LSOH Insulation	LSZH Sheath
5%	5%	10%	10%	35%	25%

The item marked \* are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

## SUBMERSIBLE FLAT CABLES

RR Kabel makes 3 Core PVC Insulated and sheathed Industrial Flat cables for Submersible Motor, working voltages upto and including 1100 Volts, as per IS 694 : 2010

Size (Sq.mm)	Configuration	Rate 100 mtr
1.5	22/0.3	6322
2.5	36/0.3	9998
4.0	56/0.3	14728
6.0	84/0.3	21364
10.0	140/0.3	37382
16.0	126/0.4	59097
25.0	196/0.4	92819

\* For XLPE Insulated Submersible Flat Cables (Cu/XLPE/PVC), contact us for pricing and availability. MOQ will be applicable.

# ONLY THE BEST SUBMERSIBLE CABLES CAN WITHSTAND THE HARSHTEST CONDITIONS.

- PVC & XLPE Insulation
- Electrolytic Grade Annealed Copper
- Better Conductivity
- CE, REACH & RoHS Compliant



## AKALMAND BANO, SAHI CHUNO.

## SHIELDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	3580	4344	5010	6346	9150	3
3 Core	4525	5619	6614	8449	12717	3
4 Core	5494	7043	8374	10843	16401	3
5 Core	6253	8190	9755	13198	20369	3
6 Core	7309	9617	11724	15379	-	3
7 Core	8106	10697	13095	17509	27490	3
8 Core	9187	12178	14828	20060	31990	2
9 Core	10157	-	-	-	-	2
10 Core	11375	14981	18456	25073	39289	2
12 Core	13178	17516	21669	29288	46579	2
14 Core	15154	20264	25185	34187	54591	1
16 Core	17019	22862	28186	38756	63542	1
18 Core	18897	25712	31463	43315	70996	1
20 Core	20898	28475	35242	50597	80339	1
22 Core	22787	31123	38568	-	-	1
25 Core	25559	35028	43477	-	-	1
27 Core	27387	37601	46729	-	-	1

Note : Please contact to Technical Cell / HO for Technical Data Sheet.

## SHIELDED ARMoured CABLES



Flexible / Stranded Bare Copper Conductor PVC / XLPE Insulated,  
 Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour And Outer PVC Sheathed  
 Industrial Instrumentation (Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	7138	8279	9179	11017	14770	5
3 Core	8596	9990	11638	13413	19131	5
4 Core	9737	11664	13743	16101	24177	3
5 Core	11169	13489	16063	19080	28399	3
6 Core	12348	15137	18231	22440	-	3
7 Core	13071	16240	19144	24506	37451	3
8 Core	15023	18129	21388	27701	42015	3
9 Core	15911	-	-	-	-	3
10 Core	17090	21083	26307	34129	51688	3
12 Core	19321	23923	29730	38579	60689	3
14 Core	21426	26865	34243	44436	67662	3
16 Core	23949	31708	36994	50002	76461	3
18 Core	27524	32468	41355	55542	84258	3
20 Core	29971	35891	45311	63136	92435	2
22 Core	30934	39264	49089	-	-	2
24 Core	-	-	53235	-	-	2
25 Core	33875	43308	54895	-	-	2
27 Core	35600	45729	60918	-	-	2

Note : Please contact to Technical Cell / HO for Technical Data Sheet.

## BRAIDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	4959	5768	6141	6950	8864	12369
3 Core	5336	6191	7629	8444	11239	16397
4 Core	6416	7869	9357	10689	13650	21429
5 Core	8035	8595	10882	12618	16683	25150
6 Core	9466	9585	11972	14744	19294	-
7 Core	9994	10306	13936	16273	20749	32771
8 Core	10709	11624	14868	18187	23969	-
9 Core	-	-	-	-	26555	-
10 Core	12793	14768	18531	22501	30085	-
12 Core	14174	16062	21255	26853	35393	53208
14 Core	-	18399	24256	30483	41062	-
16 Core	-	20712	27346	34312	45326	-
18 Core	19950	22750	30358	38017	50398	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	18730	25811	-	-
3 Core	25712	35765	-	-
4 Core	31161	43905	75112	123870

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,  
 0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.

## PAIR SHIELDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	4394	5436	10	6541	7608	10948	5
2	7131	8751	5	10847	13735	20389	3
3	9228	11651	3	14689	19008	28726	3
4	10734	14840	3	18857	24645	37526	3
5	13082	18267	3	23377	29868	45750	3
6	15267	21456	3	27570	35392	54388	2
8	19598	27068	3	34965	46365	71600	2
10	23892	33195	3	43038	57300	88763	2
12	28161	39297	3	51086	68198	105888	2
14	-	-	-	-	78229	-	1
16	36924	51877	2	67683	90721	141305	1
20	45423	64067	2	83791	112592	175693	1
24	53885	76221	2	99849	134400	210030	1

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	9253	10772	5	13195	16045	22888	2
3	11789	14664	5	18179	22423	32429	2
4	15053	18368	3	22297	29190	42448	2
5	18481	22712	3	27696	35430	51801	1
6	21745	26817	2	32781	42059	61644	1
8	28248	34990	2	42912	55279	81305	1
10	34714	43138	1	53007	68449	100916	1
12	41167	51261	1	63088	79284	120489	1
16	54350	66089	1	81519	105599	156308	1
20	67281	81946	1	101205	131286	194575	1
24	80200	97802	1	120878	156961	232830	1
25	-	-	-	125800	-	-	1

Note: The MOQ is given above, please send your requisition to Technical Cell / HO for Technical Data Sheet before finalizing the orders.

## PAIR SHIELDED ARMoured CABLES



Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire/Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Overall Pair Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	7138	8279	10	9179	11017	14770	5
2	10852	13033	5	14821	18446	25508	3
3	12729	15290	3	18294	23365	34852	3
4	15391	18763	3	22681	30744	41863	3
5	17597	22377	3	27296	34978	51536	3
6	20044	25736	3	32975	40823	60512	2
8	26205	31517	3	39124	52487	78261	2
10	28690	37856	3	47276	63871	95845	2
12	33204	44119	3	55327	74952	113290	2
14	-	-	-	-	85551	-	1
16	42306	56835	2	71770	97988	149093	1
20	51041	69069	2	87617	120567	183741	1
24	59662	81190	2	103325	142373	218213	1

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual Pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Individual Pair and Overall Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	12906	15087	5	17331	20399	27182	2
3	15822	18294	5	21299	26712	34611	2
4	18941	22782	3	27143	33660	44347	2
5	23860	28741	3	32734	38706	54680	1
6	27448	31048	2	36842	45349	64353	1
8	32126	39568	2	47200	58483	83535	1
10	38769	47973	1	57431	71491	102565	1
12	45349	56315	1	67586	84410	121493	1
16	58635	73253	1	88264	110818	160300	1
20	71618	89760	1	108422	136529	198055	1
24	84524	106203	1	128491	162151	235696	1
25	-	-	-	133499	-	-	1

Note: The MOQ is given above, please send your requisition to Technical Cell / HO for Technical Data Sheet before finalizing the orders.



## TERMS & CONDITIONS:

**GST** : The above prices are exclusive of GST.

**Packing** : Order should be in Standard packing.

**Freight** : Value upto Rs. 2,00,000/- on 'TO-PAY' basis & above on 'PAID' basis

**Note:** This is Revised Price List, hence all previous Price List & Discount will not be considered.

**THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.**



## WORLD OF EXCELLENCE



As a USD 850 + million conglomerate, we are one of the largest, diversified & most prominent brands in the Indian electrical industry, with a noteworthy presence in over 85+ countries across the world. We offer a multi faceted range of quality products through our 10 successfully operating companies, 42 marketing offices and 12 manufacturing facilities.

At RR Global, we continue to innovate to ensure only the finest products reach our customers.



Ram Ratna House, Oasis Complex, P. B. Marg, Worli, Mumbai - 400 013.

**T:** +91 - 22 - 2494 9009 / 2492 4144 • **F:** +91 - 22 - 2491 2586 • **E:** mumbai.rrkabel@rrglobal.com

305/A, Windsor Plaza, R. C. Dutt Road, Alkapuri, Vadodara - 390 007.

**T:** +91 - 265 - 2321 891 / 2 / 3 • **F:** +91 - 265 - 2321 894 • **E:** vadodara.rrkabel@rrglobal.com

---

## **R R KABEL LIMITED**

**Regd. Office :** Ram Ratna House, Oasis Complex, P. B. Marg, Worli, Mumbai - 400 013.

**Ahmedabad:** 079 - 4900 0100, **Bengaluru:** 080 - 4125 0079 / 4090 2221, **Bhubaneswar:** 0674 - 2971 231,  
**Chennai:** 044 - 2829 2329 / 2429, **Coimbatore:** 0422 - 2910 560, **Guwahati:** 0361 - 2730772,  
**Haryana:** 0130 - 2986 986, **Indore:** 0731 - 4009 863, **Jaipur:** 0141 - 2741417, **Jalandhar:** 0181 - 500 3394,  
**Ernakulam:** 0484 - 2378 782, **Kolkata:** 033 - 6607 1233 / 2262 8660, **Lucknow:** 0522 - 4113 745 / 46,  
**Madurai:** 0452 - 4370 340, **New Delhi:** 011 - 4303 8395 / 2735 5477 / 78, **Pune:** 8956 811 100,  
**Raipur:** 0771 - 2971 518, **Rajkot:** 0932 7722 501, **Secunderabad:** 040 - 2780 4098,  
**Silvassa:** 0260 - 2641 333, **Surat:** 9376 507 543, **Trichy:** 8939 830 338.

[www.rrkabel.com](http://www.rrkabel.com) • [www.rrglobal.com](http://www.rrglobal.com)

---

The technical data mentioned in the book has been derived to have the best production place. Having known that innovation has always been the base for R R Kabel products, the technical data would vary from time to time. Hence, current details should always be checked with R R Kabel for accuracy.

---

**REACH** = Registration, Evaluation, Authorisation and Restriction of Chemicals  
**RoHS** = Restriction of Hazardous Substances | **CE** = Conformance Européenne  
**ISI** = Indian Standard Institution